TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

IMPORTANT:
THIS DRAWING SHALL BE USED IN
COMBINATION WITH THE GENERAL
NOTES AT THE BEGINNING OF
STANDARDS MD 104.00.

NOTES:
THIS TYPICAL ALSO APPLIES TO
DIVIDED UNCONTROLLED HIGHWAYS.
EXCEPT AS OTHERWISE STATED
IN GENERAL NOTES.

SYMBOL SIGNS TO REFLECT ACTUAL NUMBER OF THROUGH LANES. USE RECTANGULAR SHAPED SIGNS FOR THREE OR MORE DIVIDED THROUGH LANES

THE "BEGIN AND END SHOULDER USE" SIGNS SHOULD BE OMITTED WHEN THE SHOULDER CANNOT BE DIFFERENTIATED FROM THE NORMAL TRAVEL PATH.

ROAD WORK (OPTIONAL) END SHOULDER USE 1 **BEGIN** SHOULDER USE SHOULDER TAPER 1/3 L 1 1 DIVIDE Z 介1介 $\{ (1, 1) \}$ ROAD WORK

CHANNELIZING DEVICES SIGN SUPPORT FACE OF SIGN DIRECTION OF TRAFFIC WORK SITE

KEY:

| SPECIFICATION 104 | CATEGORY CODE ITEMS |
|-------------------|---------------------|
| APPROVED | MA |

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

APPROVAL • SHA APPROVAL • FEDERAL HIGHWAY ADMINISTRATION

APPROVAL • 9-10-96 APPROVAL • 9-27-96

REVISED 10-1-01 REVISED

REVISED REVISED

REVISED

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

LANES DIVIDE/EXP-FREEWAY

GREATER THAN 40 MPH/15 MIN - 12 HRS.

OR DAYTIME ONLY

STANDARD NO. MD 104.51